


Plank 138

13 mm Click

Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	13 x 138 x 2200 mm
Toplayer:	about 2.5 mm
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 2.5 mm Middlelayer 8.8 mm Bottomlayer 1.7 mm
Boards/ m ² per carton:	10/ 3.04
Cartons/ m ² per pallet:	42/ 127.68
Slotted top layers per carton/ minimum length (mm):	3/ 600
Weight per carton/ pallet in kg:	23/ 966
Floor heating systems:	Well suitable to very well suitable
Fire behavior ¹⁾ :	Dfl-s1
Content of formaldehyd ²⁾ :	E1
Content of pentachlorophenol (PCP) ²⁾ :	no performance detected
Density kg/ m ³ ²⁾ :	about 600
Antislip performance:	Live Satin USRV 25 ²⁾ Live Matt USRV 29 ²⁾ Live Natural USRV 40 ²⁾
Abrasion resistance:	Live Satin 70/ 1100 ³⁾ Live Satin 100 ⁴⁾
Thermal conductivity ²⁾ :	0.15 W/ (m·K)
Areal thermal resistance ⁵⁾ :	0.093 m ² · K/ W



DOP 4658



www.blauer-engel.de/uz176

CE
BOEN AS
EN 14342



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696,

⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524